

Lembar data produk

Spesifikasi



EcoStruxure Panel Server - advanced datalogger, energy server, 24 VDC

PAS800L

Main

Range	EcoStruxure
product name	Panel Server Advanced
Product or component type	Gateway
Device short name	PAS800L
Device application	Energy server Data logger
[Us] rated supply voltage	24 V DC
Communication gateway	Ethernet TCP/IP to wireless devices Ethernet/serial

Complementary

Maximum power consumption in W	3.5 W 24 V
Communication network type	Ethernet, 10/100BASE-T Wi-Fi infrastructure2.4 GHz Wi-Fi infrastructure5 GHz Wi-Fi access point2.4 GHz Wireless, IEEE 802.15.4 Modbus RTU, Modbus RTU client even/odd or none parity, at 1.2...115.2 kbit/s
Communication port protocol	Modbus TCP DHCP HTTPS NTP/SNTP IPv4 IPv6 TCP/IP
Communication port support	2 RJ45: ETHERNET Screw terminal block: RS485
Number of server device(s)	32 Modbus RTU product(s) 128 Modbus TCP/IP product(s) 40 wireless product(s) - mixed 85 wireless product(s) - depending on configuration
Number of devices	64 Modbus TCP/IP
Memory capacity	32 GB eMMC 512 MB NAND
Number of inputs	2 digital
Connections - terminals	Discrete I/O: screw terminal block (top) 0.14...1.5 mm² cable(s) Power supply: screw terminal block (top) 1.5...2.5 mm² cable(s) Communication: screw terminal block (bottom) 0.14...1.5 mm² cable(s)
Tightening torque	Discrete I/O: 0.25 N.m Power supply: 0.6 N.m Communication: 0.25 N.m

Disklaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Wire stripping length	Power supply: 7 mm Communication: 7 mm Discrete I/O: 7 mm
Number of connectors	2 RP-SMA for Wi-Fi and IEEE 802.15.4
Connector type	connector(s)1 x RP-SMA, Wi-Fi for antenna bottom connector(s)1 x RP-SMA, IEEE 802.15.4 for antenna top
Mounting mode	Clip-on
Mounting support	DIN rail
Product certifications	CE cULus CB RCM UKCA FCC IC DNV Marine ANSI RF IACS E10
Standards	IEC 61010 IEC 61010-1 IEC 61010-2-201 UL 61010 UL 61010-1 UL 61010-2-201 EN 61010-1 EN 61010-2-201 CAN/CSA C22.2 No. 61010-1-12 CAN/CSA C22.2 No. 61010-2-201 IEC 62974-1 IEC 61326-1 EN 61326-1 ETSI EN 301 489-1 ETSI EN 301 489-17 EN 301-893 EN 55032 CISPR 11 ETSI EN 300 328 IEEE 802.15.4 IEEE 802.11a/b/g/n IEEE 802.3 af/at FCC CFR 47 part 15 class A EN 62311 IEC 62311 IEC 60945 EN 62974-1
Depth	70.2 mm
Height	93 mm
Width	72 mm
Net weight	186 g
Data recording	Historical dashbaording and trending 3 years data logs
Data buffer for data publication (cloud, SFTP, HTTPS) depending on network	3 month(s)
Function available	Embedded web page for configuration and upgrade Diagnosis capabilities Diagnostic report Diagnostics on communication Embedded data logger Event Logger Energy management With integrated web server Firmware update Configurable event Backup/restore configuration CSV export
Product specific application	Wireless Schneider Electric devices ecosystem

Topology	Separated Ethernet network Switched Ethernet network
Web services	HTTPS server SFTP publication (CSV / JSON) HTTPS publication (CSV / JSON) Alarm notification by e-mail
Communication service	Device Profile for Web Services (DPWS) Modbus TCP client Modbus TCP server SNTP client DHCP client DHCP server Web server (energy & operation efficiency) RSTP
Commissioning interface	EcoStruxure Power Commission desktop EcoStruxure Power Commission Mobile (through Wi-Fi Access point) EcoStruxure Power Commission web (for third party device integration) Web page
Realtime clock	With RTC-battery set With user calibration
Time synchronisation protocol	NTP SNTP
Range compatibility	EcoStruxure Facility Expert EcoStruxure Building Operation EcoStruxure Power Operation EcoStruxure Power Monitoring Expert EcoStruxure Asset Advisor EcoStruxure Energy Hub EcoStruxure Resource Advisor Third party SCADA
Communication interface	Wired and wireless

Environment

Relative humidity	5...95 %
IP degree of protection	IP40 (front face) IP20 (casing)
Ambient air temperature for operation	-25...70 °C at < 2000 m -25...60 °C at 2000...4000 m
Derating factor	With temperature derating of -1 °C per 200 m 4000...5000 m
Ambient air temperature for storage	-40...85 °C
pollution degree	3
Operating altitude	< 5000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	9.000 cm
Package 1 Length	11.000 cm
Package 1 Weight	279.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Height	30.000 cm

Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.159 kg

Environmental Data

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

[Environmental Data dijelaskan >](#)

[Bagaimana kami menilai keberlanjutan produk >](#)

Jejak lingkungan	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	51
Environmental Disclosure	Product Environmental Profile

Use Better

Bahan dan Pengemasan	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	3f06bd1f-f04f-4301-bb9a-5353a242283d
China RoHS Regulation	China RoHS declaration
Halogen content performance	Halogen free plastic parts & cables product
PVC free	Yes

Use Again

Repak dan remanufaktur	
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins