

Lembar data produk

Spesifikasi



current transformer tropicalised DIN
mount 400 5 cables d. 27 - bars
10x32 15x25

METSECT5MA040

Main

Range	PowerLogic
product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 at 10 VA Class 1 at 12 VA
[In] rated current	400 A

Complementary

Current transformer type	Tropicalised for busbar and cable
Current transformer ratio	400/5
[Ith] conventional free air thermal current	24 kA
Dynamic withstand current	2.5 Ith
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	Clip-on By screws Insulated locking screw
Mounting support	DIN rail Busbar Mounting plate
Width	Outside: 56 mm
Height	Outside: 80 mm
Depth	Frame : 43 mm Total : 63 mm
Diameter	27 mm
Net weight	0.328 kg
[Uimp] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B
Cable outer diameter	27 mm
Opening of bars	25.5 x 15.5 32.5 x 10.5
Sealing	Without

Disklaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Environment

Standards	VDE 0414 IEC 61869-2
Product certifications	EAC CE
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	7.2 cm
Package 1 Length	9.4 cm
Package 1 Weight	322 g
Unit Type of Package 2	S03
Number of Units in Package 2	35
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	11.71 kg

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

[Environmental Data dijelaskan >](#)

[Bagaimana kami menilai keberlanjutan produk >](#)

Use Better

 Bahan dan Pengemasan	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Again

 Repak dan remanufaktur	
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins