

# Lembar data produk

Spesifikasi



## PM5110 powermeter w modbus - upto 15th H - 1DO 33alarms - flush mount

METSEPM5110

### Main

Range	PowerLogic
product name	PowerLogic PM5000
Device short name	PM5110
Product or component type	Power meter

### Complementary

Power quality analysis	up to the 15th harmonic
Device application	Power monitoring
Type of measurement	Current Voltage Frequency Power factor Energy Active and reactive power
supply voltage	90...450 V AC 45...65 Hz 100...300 V DC
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
type of network	1P + N 3P + N 3P
Maximum power consumption in VA	11 VA at 415 V
Ride-through time	80 ms 120 V AC typical 100 ms 230 V AC typical 100 ms 415 V AC typical 50 ms 125 V DC typical
Display type	Monochrome graphic LCD
Display resolution	128 x 128 pixels
Sampling rate	64 samples/cycle
Measurement current	50...8500 mA
Analogue input type	Voltage (impedance 5 MOhm) Current (impedance <= 0.3 mOhm)
Measurement voltage	35...760 V AC 45...65 Hz between phases 20...440 V AC 45...65 Hz between phase and neutral
Frequency measurement range	45...65 Hz
Number of inputs	0

<b>Measurement accuracy</b>	Active energy +/- 0.5 % Reactive energy +/- 2 % Active power +/- 0.5 % Apparent power +/- 0.5 % Frequency +/- 0.05 % Power factor +/- 0.5 Current +/- 0.5 % Voltage +/- 0.5 % Apparent energy +/- 0.5 % Reactive power +/- 2 %
<b>Accuracy class</b>	Class 0.5S active energy conforming to IEC 62053-22
<b>Number of outputs</b>	1 digital
<b>Communication port protocol</b>	Modbus RTU and ASCII at 9.6, 19.2 and 38.4 kbauds even/odd or none - 2 wires, insulation 2500 V JBUS
<b>Communication port support</b>	RS485
<b>Data recording</b>	Time stamping Min/max of instantaneous values
<b>Connections - terminals</b>	Voltage circuit: screw terminal block4 Control circuit: screw terminal block2 Current transformer: screw terminal block6 Input/output circuit: screw terminal block6 RS485 link: screw terminal block4
<b>Mounting mode</b>	Flush-mounted
<b>Mounting support</b>	Framework
<b>Standards</b>	UL 61010-1 EN 50470-3 EN 50470-1 IEC 62053-22:2020 IEC 60529 IEC 62053-24 IEC 61557-12:2015 IEC 62053-23:2020 IEC 62052-11:2020 IEC 62052-31:2015
<b>Product certifications</b>	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1
<b>Width</b>	96 mm
<b>Depth</b>	72 mm
<b>Height</b>	96 mm
<b>Net weight</b>	380 g

## Environment

<b>Electromagnetic compatibility</b>	Voltage dips and interruptions immunity test class A conforming to IEC 61000-4-11 Limits for harmonic current emissions class A conforming to IEC 61000-3-2 Electrostatic discharge level 4 conforming to IEC 61000-4-2 Conducted RF disturbances level 3 conforming to IEC 61000-4-6 Magnetic field at power frequency level 4 conforming to IEC 61000-4-8 Conducted and radiated emissions - test level: 150 kHz...80 MHz class B conforming to EN 55022 Immunity to conducted disturbances - test level: 150 kHz...80 MHz conforming to IEC 61000-4-6 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Surge immunity test class B conforming to IEC 61000-4-5 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11
<b>IP degree of protection</b>	IP54 display: conforming to IEC 60529 IP30 rear: conforming to IEC 60529
<b>Relative humidity</b>	5...95 % at 50 °C non-condensing
<b>Pollution degree</b>	2

<b>Ambient air temperature for operation</b>	-25...70 °C meter -20...70 °C display -25...-20 °C (with reduced performance) display
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Operating altitude</b>	2000 m CAT III

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	16.000 cm
<b>Package 1 Width</b>	12.600 cm
<b>Package 1 Length</b>	12.600 cm
<b>Package 1 Weight</b>	478.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	12
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	6.345 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	96
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	61.820 kg

## Contractual warranty

<b>Warranty</b>	12 months
-----------------	-----------

## Environmental Data

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

[Environmental Data dijelaskan >](#)

[Bagaimana kami menilai keberlanjutan produk >](#)

### Jejak lingkungan

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Bahan dan Pengemasan

[EU RoHS Directive](#)

Compliant with Exemptions

## Use Again

### Repak dan remanufaktur


[Circularity Profile](#)

[End of Life Information](#)

Take-back

No

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins